


REVISIONS			
ISS	ZONE	DESCRIPTION\PER REQUEST	DATE
V	OPEN	對客戶公開圖紙	
	OPEN	對供應商公開圖紙	
	CLOSED	僅限廠內使用	

8	插針(PIN)	H59-1	鍍金(GOLD)	5	
7	插孔(FEMALE PIN)	PHOSPHOR BRONZE	鍍金(GOLD)	5	
6	塑膠(INSULATOR)	PA(94V0)	黑色(BLACK)	1	
5	鋼片(LATCH)	SUS304		1	
4	按鍵(PUSH BUTTON)	SUS304		1	
3	鋼片固定片(FIXED PLATE)	PA(94V0)	黑色(BLACK)	1	
2	後蓋(BACK COVER)	PA(94V0)	黑色(BLACK)	1	
1	包膠面板(ENCAPSULATE PANEL)	PA(94V0)+TPE(94HB)	黑+橙(BK+OR)	1	
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS		APPROVED	DATE
UNLESS OTHERWISE SPECIFIED TOLERANCES		CHECKED	DATE
ANGLES = $\pm 5^\circ$ UP TO 6 = ± 0.2 6-40 = ± 0.4 40-120 = ± 0.6 120-315 = ± 1 ABOVE 315 = ± 1.6		DRAWN	DATE
THIRD_ANGLE		FILE NO.	
SCALE		ERP LINK:	
1.5/1			

		TITLE	
		WATER PROOF 5P XLR FEMALE SOCKET	
PART NO.		REV.	A1
XL15FB-WP-G			